



# Do I need to configure the IP address when connecting the optical port of the switch to the OLT

Next, you should assign a management IP address. This is a fixed IP address that allows you to access the OLT from your network, without having to connect with a cable every time. It ...

Add the port connected to OLT as a tagged port (Here is port 9), and add the port connected to the IPTV as an untagged port (Here is port 4). ...

The ONU is connected to the OLT through the optical splitter and optical fiber, and the OLT terminates the PON protocol. When a packet enters the GPON network, the packet is converted ...

About : Accessing an OLT (Optical Line Terminal) remotely using a static IP involves configuring the OLT's network settings and configuring port forwarding on the router.

Next, you should assign a management IP address. This is a fixed IP address that allows you to access the OLT from your network, without having to ...

Configuring a BDCOM OLT might seem complicated, but with the right guidance, anyone can do it. This guide will walk you through the process, step-by-step, in a way that's easy to ...

This document provides instructions for configuring an optical line terminal (OLT) including: 1. Configuring the OLT's network settings like IP address. 2. Accessing ...

The default IP address of TP-Link P1201 is 192.168.1.100. You will need to set your computer IP address to the same subnet with the 192.168.1.0/24. (e.g. 192.168.1.200) Then connect your PC to the MGMT ...

Connect Ethernet 2/0/1 of the switch with a multicast source, and connect port OLT 3/0/1 of the OLT with an ONU, which is bound to ONU 3/0/1:1, through an optical splitter.

Configure network settings: Access the GPON modem's configuration page by entering its IP address into a web browser. Use the default username and password provided by your service ...

This document provides instructions for configuring an optical line terminal (OLT) including: 1. Configuring the OLT's network settings like IP address. 2. Accessing the OLT's web interface for ...

Add the port connected to OLT as a tagged port (Here is port 9), and add the port connected to the IPTV as an untagged port (Here is port 4). Configure the corresponding PVIDs for ...



## Do I need to configure the IP address when connecting the optical port of the switch to the OLT

The IP Address to log into the router is 192.168.11.1 LAN to WAN. You may use a fixed IP (ex.: 1 Log in and set the MAC address After the configuration is done, initiate the switch and plug in the XGS-PON ...

Web: <https://maxtools.co.za>

