



Low Noise Fiber Optic Heat Shrink Tubing for Data Center Interconnection

The COMPAQ CFOT Series is a medium-wall heat shrinkable tubing designed specifically for fibre optic splice closures in telecom, broadband, and data network applications.

The heat shrink tubes features: Cross-linked polyolefin and hot fusion material with a stainless reinforced steel rod. Preserves optical transmission performance and provides safe protection for fiber optic ...

Steel or all-dielectric heat shrink sleeves by Corning, Raychem, Mooseline. Single or ribbon fiber splices. 1.5, 2.0, 3.0mm in diameter, 25, 40, 60mm in length.

Cross-linked tubing which arrives expanded to be applied to the juncture or cable to be sealed and recovers to its smaller diameter in the presence of heat.

Protect your fiber optic application against abrasion and mechanical wear and secure your investment with our fiber optic heat-shrink tubing!

A specially designed cross-linked Clear Heat Shrinkable tubing, with Clear fusion tubing liner, providing protection to fiber optical splices. Available with single fiber and ribbon fiber. Customized designs are ...

With 2:1 shrink ratio, this high-performance flexible fluoropolymer tubing is designed for jacketing and bundling of wires to form light-duty harnesses, especially where low profile, abrasion resistance, and ...

Shop DigiKey's large in-stock selection of Heat Shrink Tubing. View inventory, pricing and order now for same day shipping!



Low Noise Fiber Optic Heat Shrink Tubing for Data Center Interconnection

Web: <https://maxtools.co.za>

