



RoHS Optical Hybrid Cable QSFP-DD

Discover how we power manufacturing and research across the world's most innovative markets -- from smartphones to EVs, from semiconductor wafers to medical diagnostics. This product is well suited ...

It provides a QSFP-DD-to-QSFP-DD copper direct-attach solution. QDD-400-CuxM cables are suitable for very short links and offer a cost-effective way to establish a 400-Gigabit link between ...

Description The 400G OSFP-QSFPDD passive copper cable assembly feature sixteen differential copper pairs, providing eight data transmission channels at speeds up to 56Gbps(PAM4) ...

Amphenol's QSFP-DD Linear Pluggable Optical (LPO) Transceiver delivers low-latency, high-bandwidth PCIe® Gen 5.0 over optical link, enabling scalable server disaggregation and efficient rack-to-rack ...

Amphenol's QSFP DD (Double Density) copper cable assemblies double the number of channels from 4 to 8 lanes when compared to the existing QSFP cabling systems, enabling more ...

Maximum link length of 70m on OM3 or 100m on OM4 Management interface compliant with CMIS 4.0 Hot pluggable QSFP-DD form factor Commercial operating case temperature range: 0 to 70°C RoHS ...

It provides a QSFP-DD-to-QSFP-DD copper direct-attach solution. They are suitable for very short links and offer a cost-effective way to establish a 400-Gigabit link between QSFP-400G ports of ...

SFP, QSFP, QSFP-DD, OSFP ACTIVE OPTICAL CABLE ASSEMBLIES Our active optical cable assembly portfolio provides improved cable flexibility and longer reach as compared to both ...

Description 400G QSFP-DD to 400G QSFP-DD Active Optical Cable enables low-power, high-reliability and high-speed interconnections over very thin copper cables without using any optical components.

3. SELECTION GUIDE QSFP-DD er optic cable assemblies. This specification aims to provide an easy-to-use selection guide for fiber optic cables used with standard TX s of optical transceivers. High ...



RoHS Optical Hybrid Cable QSFP-DD

Web: <https://maxtools.co.za>

